

It's all about performance.



☉ Galaxie™

Out of this world looks and performance with great heat control and signal friendly design

When you want to make a statement, Solar Gard® Galaxie™ delivers with its head turning finish and bold black look. Superior quality and exceptional performance will enhance your driving experience and protect you from the sun's heat and damaging UV rays. Industry leading clarity, for unaltered visibility and safe driving, make Galaxie the ideal window film for looking and keeping cool.

Features and benefits:

- Bold black tint with various shades to choose from
- Blocks more than 99% of UV rays to protect you, your passengers and your car interior
- Signal friendly, including: GPS, satellite radios, cellular phones and tire pressure monitoring systems
- Excellent film clarity for unaltered visibility
- Superior glare reduction for safe and comfortable driving
- Warranted against excessive fading or color change
- Outstanding scratch resistant coating for maintenance free operation



Performance specs:

	% Visible light transmittance @550nm	% Visible light reflectance out	% Ultraviolet (UVA/UVB) rejected	Sun protection factor (SPF)	% Total solar energy rejected
Galaxie 50	54	7	>99	285+	28
Galaxie 35	39	6	>99	285+	32
Galaxie 20	22	6	>99	285+	37
Galaxie 5	5	5	>99	285+	42

Performance results were generated with LBNL Windows 5.2 using 1/8" (3mm) clear glass and have been measured, calculated and reported in accordance with ASTM, ASHRAE and AIMCAL standards.

All Solar Gard films offer 285+ SPF.

SOLAR ENERGY TECHNICAL DEFINITIONS

Visible light transmittance

The percent of total visible light that is transmitted through the window film/glass system. The lower the number, the less visible light transmitted.

Visible light reflectance out

The percent of total visible light that is reflected by the window film/glass system. The lower the number, the less visible light reflected.

Ultraviolet rejected

The percent of ultraviolet (UV) that is blocked by the window film/glass system. The higher the number, the less UV transmitted.

Sun protection factor

The SPF rating is a measure of the protection from UVB ultraviolet radiation caused by exposure to the sun. It is calculated by comparing the amount of time needed to produce a sunburn on protected skin to the amount of time needed to cause a sunburn on unprotected skin. Solar Gard Galaxie window films block up to 99% of both UVA and UVB.

Total solar energy rejected

The percent of total solar energy (heat) rejected by the window film/glass system. The higher the number, the more total solar energy (heat) rejected.

www.solargard.com/us

Saint-Gobain Performance Plastics
4540 Viewridge Avenue
San Diego, CA 92123
Tel: 877-273-4364
E-mail: info@solargard.com

SK0168GX 01/12

© Copyright 2012, Saint-Gobain Performance Plastics Corporation and/or its affiliates
All Rights Reserved • www.solargard.com

 Please recycle

